

Yellow/black exhaust hose (temp.resistance +150°C)

With steel coil

Prod. no:	Hose-diameter	Length
EH-75-5	75 mm	5 m
EH-100-5	100 mm	5 m
EH-125-5	125 mm	5 m
EH-150-5	150 mm	5 m
EH-75-7.5	75 mm	7.5 m
EH-100-7.5	100 mm	7.5 m
EH-125-7.5	125 mm	7.5 m
EH-150-7.5	150 mm	7.5 m
EH-75-10	75 mm	10 m
EH-100-10	100 mm	10 m
EH-125-10	125 mm	10 m
EH-150-10	150 mm	10 m



Silvergrey exhaust hose (temp.resistance +650°C)

With steel coil

Prod. no:	Hose-diameter	Length
ET-75-5	75 mm	5 m
ET-100-5	100 mm	5 m
ET-125-5	125 mm	5 m
ET-150-5	150 mm	5 m
ET-75-7.5	75 mm	7.5 m
ET-100-7.5	100 mm	7.5 m
ET-125-7.5	125 mm	7.5 m
ET-150-7.5	150 mm	7.5 m
ET-75-10	75 mm	10 m
ET-100-10	100 mm	10 m
ET-125-10	125 mm	10 m
ET-150-10	150 mm	10 m



Yellow/black exhaust hose (temp.resistance +200°C)

With steel coil

Prod. no:	Hose-diameter	Length
EG-75-5	75 mm	5 m
EG-100-5	100 mm	5 m
EG-125-5	125 mm	5 m
EG-150-5	150 mm	5 m
EG-75-7.5	75 mm	7.5 m
EG-100-7.5	100 mm	7.5 m
EG-125-7.5	125 mm	7.5 m
EG-150-7.5	150 mm	7.5 m
EG-75-10	75 mm	10 m
EG-100-10	100 mm	10 m
EG-125-10	125 mm	10 m
EG-150-10	150 mm	10 m



Crush-proof hose ends with nylon coil.

Straight- and Y-shaped adapters.

Prod. no:	Hose-diameter	Length
RS-75	75 mm	2,5 m
RS-100	100 mm	2,5 m
RS-125	125 mm	2,5 m
RS-150	150 mm	2,5 m
YS-75	75 mm	2x2,5 m
YS-100	100 mm	2x2,5 m
YS-125	125 mm	2x2,5 m
YS-150	150 mm	2x2,5 m



Rubber nozzle

Rubber nozzle with probe-opening.

Prod. no:	Hose-diameter	Nozzle-diameter
REN-75-115	75 mm	115 mm
REN-100-115	100 mm	115 mm
REN-100-160	100 mm	160 mm
REN-125-160	125 mm	160 mm
REN-150-160	150 mm	160 mm



Yellow/black exhaust hose (temp.resistance +300°C)

With steel coil

Prod. no:	Hose-diameter	Length
EF-75-5	75 mm	5 m
EF-100-5	100 mm	5 m
EF-125-5	125 mm	5 m
EF-150-5	150 mm	5 m
EF-75-7.5	75 mm	7.5 m
EF-100-7.5	100 mm	7.5 m
EF-125-7.5	125 mm	7.5 m
EF-150-7.5	150 mm	7.5 m
EF-75-10	75 mm	10 m
EF-100-10	100 mm	10 m
EF-125-10	125 mm	10 m
EF-150-10	150 mm	10 m



Rubber nozzle

Rubber nozzle with probe-opening and vise grip.

Prod. no:	Hose-diameter	Nozzle-diameter
REG-75-115	75 mm	115 mm
REG-100-115	100 mm	115 mm
REG-100-160	100 mm	160 mm
REG-125-160	125 mm	160 mm
REG-150-160	150 mm	160 mm



Rubber nozzle

Rubber nozzle with probe-opening and spring clip.

Prod. no:	Hose-diameter	Nozzle-diameter
REC-75-115	75 mm	115 mm
REC-100-115	100 mm	115 mm
REC-100-160	100 mm	160 mm
REC-125-160	125 mm	160 mm
REC-150-160	150 mm	160 mm



Metal nozzle

Metal nozzle with rubber lid and probe-opening.

Prod. no:	Hose-diameter	Nozzle-diameter
MEN-75-100	75 mm	100 mm
MEN-100-100	100 mm	100 mm
MEN-125-125	125 mm	125 mm
MEN-125-150	125 mm	150 mm
MEN-150-150	150 mm	150 mm
MEN-150-200	150 mm	200 mm



Nozzle, Grabber

A pneumatic exhaust pipe connector for quick connection of the exhaust hose. Manual hand valve is included. Pneumatic controlled by air from the local net. The compressed air pressure is reduced with PlymoVent regulator RM-15.

Prod. no:	Diameter hose con.	Diameter rubber bladder
GN-75-100	75 mm	100 mm
GN-100-100	100 mm	100 mm
GN-100-120	100 mm	120 mm
GN-100-160	100 mm	160 mm
GN-125-160	125 mm	160 mm
GM-125-200	150 mm	200 mm
GN-150-160	150 mm	160 mm
GN-150-200	150 mm	200 mm



Regulator, Grabber

Reduces air pressure from the local net to the working pressure of the Grabber.

Prod. no: RM-15



Stacker

Nozzle for upward turned exhaust pipe.


Prod. no:	Hose-diameter	Nozzle-diameter
STACK-125-200	125 mm	200 mm
STACK-150-250	150 mm	250 mm
TH-90	Teleskopik handle	1,7-3,2m
SC-90	Spring clip for Stacker	



Fan mounting kit

To be used when mounting a fan to exhaust reel. Consists of bracket, rubber ring and fan socket.

Prod. no: FMA-80



Fans

For mounting spring and power operated exhaust reels. Used with fan mounting kit FMA above.

FUA-1300 for exhaust reels Ø 75, 100mm, FUA-2100 for exhaust reels Ø 125, 150mm.

Prod. no: FUA-1300
FUA-2100



Starter SA-24

Starter for fan. Complete with built-in contactor and transformer. It must be fitted with relevant motor overload (not included). Power supply: 3~230/400 V.

Prod. no: SA-24/75



Automatic damper

Fully automatic, motorised damper, Ø 160 mm, with built-in energy saver. Adjustable delay 7 sec.-6 min. Can be complemented with a switch assembly (S-100) for manual control. Power supply: 1~230 V.

Prod. nr: ASE-12-E



Control unit M-1000

For a central fan with several extractors. To be used with PlymoVents Automatic damper. Starts/stops the central fan automatically when any of the extractors are used. Delay 15 sec. The motor overload (not included) is to be sized according to the central fan used. Power supply: 1~230/400 V.

Prod. no: M-1000



Control box PCU-1000

Fully automatic control box for operation of fan. The fan can be controlled manually or by using the pressure sensor PC-500. This product can also be combined with PlymoVent's automatic damper ASE-12-E. Adjustable overrun period of 7sec.-6 min. Built-in contactor should be equipped with suitable overload (not included). Power supply: 3~230/400 V.

Prod. no: PCU-1000



pressure sensor PC-500

This sensor, which is used for starting the fan, recognises any pressure change in ducts when a vehicle starts up. This device is intended for use together with **PCU-1000**.

Prod. no: PC-500



Swinging arm

Swinging suspension arm and spring operated exhaust reel will cover a large area. The exhaust reel can either be connected to a central ducting or to a separate fan. The wall mounting bracket is prepared for the mounting of a fan.

Prod. no:	Length
EB-2,5	2,5 m
EB-3,5	3,5 m
EB-4,5	4,5 m

