SUS-5/203

FLEXIBLE EXTRACTION HOSE

The SUS-5/203 is a flexible hose with a suction nozzle, fitted with a magnetic foot. It is supplied with a hose clamp and can be enlarged by an extension hose.

The SUS-5/203 is to be connected to a mobile welding fume extractor.



APPLICATIONS

The SUS-5/203 is intended to be used for the following applications:

- MIG-MAG/GMAW welding
- TIG welding
- FCAW welding
- stick/MMAW welding

Do not use the SUS-5/203 for the following applications or in the following circumstances:



- aluminium laser cutting
- extraction of aggressive fumes and gases (e.g. from acids, from alkaline, from soldering paste containing lithium)
- extraction of hot gases (more than 45°C/113°F continuously)
- grinding aluminum and magnesium
- flame spraying
- extraction of cement, saw dust, wood dust etc.
- sucking cigarettes, cigars, oiled tissues and other burning particles, objects and acids
- explosive environments or explosive substances/gases

SPECIFICATIONS

Physical dimensions and properties	
5 m (16.5 ft)	
203 mm (8 in.)	
• black RAL 9005 • grey RAL 7024	
steel synthetic material with external metal spiral reinforcement, wear resistant	
9,5 kg (21 lbs)	
max. 1600 m³/h (942 CFM)	
■ Ambient conditions	
• 5°C (41°F) • 20°C (68°F) • 45°C (113°F)	

Max. relative humidity	80%
Outdoor use allowed	no
Storage conditions	• 5-45°C (41-113°F)
	• relative humidity max. 80%
■ Product combinations	
MFD, MFS, MFE	mobile unit
Available options	
EXS-5/203	extension hose 5 m/16.5 ft
	(max. hose length:
	total 10 m/33 ft)
■ Scope of supply	
Extraction hose with nozzle - Hose clamp	
Order information	
Article number	7900068030
Number/package	1
■ Shipping data	
Gross weight	10 kg (22 lbs)
Packing dimensions	20 x 25 x 135 cm
Packing dimensions	20 x 25 x 135 cm (7.9 x 9.8 x 53.2 in.)
Packing dimensions Max. number/pallet	
	(7.9 x 9.8 x 53.2 in.)

Product type Article no. Product category SUS-5/203 7900068030

080710/B

Always check the latest version on **www.plymovent.com**.